## **A6/V6 Option Switch Settings: 1**

Supported bill MXP 20, 50, 100, 200 USD 1, 5, 10, 20 8bills.

A6/V6 dip-switch settings and functions:

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW1	SW2	SW3	SW4
	Reject MXP 20 & USD 1	ON											
*	Accept MXP 20 & USD 1	OFF											
	Reject MXP 50 & USD 5		ON										
*	Accept MXP 50 & USD 5		OFF										
	Reject MXP 100 & USD 10			ON									
*	Accept MXP 100 & USD 10			OFF									
	Reject MXP 200 & USD 20				ON								
*	Accept MXP 200 & USD 20				OFF								
	Accept Mexico Pesos and US Dollars (Note 1)					ON							
*	Accept Mexico Pesos Only (Note 1)					OFF							
	Reserved						ON						
*	Reserved						OFF						
	Harness Disable							ON					
*	Harness Enable							OFF					
	Inhibit Active High		ON										
*	Inhibit Active Low	OFF											
*	1 pulse / MXP 10	OFF OFF											
	2 pulse / MXP 10	ON OFF											
	5 pulse / MXP 10	OFF ON											
	10 pulse / MXP 10	ON ON											
*		50ms on / 50ms off							OFF	OFF			
	Interface Timing Conversion	60ms on / 300ms off							ON	OFF			
	<b>5</b> 22 7 2000	30ms on / 50ms off							OFF	ON			
		150m	s on	/ 150	ms of	f						ON	ON

Factory configuration has all switches in the OFF position.

Note: (1) For Accepting US Dollars, make sure you have dip 5 set to ON position. (Exchange rate on USD to MXP is 1:10)

- (2) Reset the bill acceptor after setting the dip switch.
- (3) SW7 and SW8 of the 8-switch DIP and the 4-switch DIP are for pulse protocol only.

## A6 Interface Settings: 2(Pulse/RS232)

	INTERFACE	SW1	SW2	SW3	SW4
*	Credit-Pulse Normal HIGH	ON			
	Credit-Pulse Normal LOW	OFF			
*	Pulse Mode		ON		
	RS232 Interface		OFF		
				ON	
*	Reserved			OFF	
	Neserveu			ON	
*					OFF

## ★ Manufacture setting

	INTERFACE	SW1	SW2	SW3	SW4
	Reserved	ON			
*	Reserved	OFF			
	Pulse Mode		ON		
*	RS232 Interface		OFF		
				ON	
*	Reserved			OFF	
	Neserveu		ON		
*					OFF

<sup>★</sup> Manufacture setting

## V6 Interface Settings: 2(M.D.B)

*	INTERFACE	SW1	SW2	SW3	SW4
	Reserved	ON			
	Reserved				
	Reserved		ON		
*	M.D.B Interface		OFF		
				ON	
*	Reserved			OFF	
				ON	
*			OFF		

<sup>★</sup> Manufacture setting