

S6 Option Switch Settings : 1 (12V DC)**Supported bill US\$ 1, 5, 10, 20 4 bills.**

S6 dip-switch settings and functions:

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW1	SW2	SW3	SW4
★	Reject US\$ 1	ON											
	Accept US\$ 1	OFF											
	Reject US\$ 5		ON										
★	Accept US\$ 5		OFF										
	Reject US\$ 10			ON									
★	Accept US\$ 10			OFF									
	Reject US\$ 20				ON								
★	Accept US\$ 20				OFF								
	ES. Quick sleep					ON							
★	ES. Delay to sleep					OFF							
	High Acceptance						ON						
★	High Security						OFF						
	Harness Disable							ON					
★	Harness Enable							OFF					
	★★ Inhibit Active High								ON				
	★ Inhibit Active Low								OFF				
★	1 pulse / one dollar									OFF	OFF		
	2 pulse / one dollar									ON	OFF		
	4 pulse / one dollar									OFF	ON		
	20 pulse / one dollar									ON	ON		
★	Interface Timing Conversion	50ms on / 50ms off										OFF	
		100ms on / 100ms off										ON	
	Factory define(Always ON)												ON

★ Manufacture setting

◆ Harness disable : B.A. will not accept inhibit signal.

Harness enable : B.A. will accept inhibit signal.

◆ ES. Quick sleep : Quick sleep on Exception status.

ES. Delay to sleep : Delay to sleep on Exception status.

◆ The SW4 of the 4-dips must always be on.

S6 Interface Settings: 2

	INTERFACE	SW1	SW2	SW3	SW4
★	Credit-Pulse Normal HIGH	ON			
	Credit-Pulse Normal LOW	OFF			
★	Pulse Mode		ON		
	RS232 Interface		OFF		
★	Reserved			ON	
				OFF	
★					ON
★					OFF

★ Manufacture setting