

## TAO-V-USD6

### TAO-V Option Switch Settings: 1(Pulse/MDB)

Supported bill US\$ 1, 5, 10, 20, 50, 100 6bills.

TAO-V dip-switch settings and functions:

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW1	SW2	SW3	SW4
★ Reject US\$ 1	ON											
★ Accept US\$ 1	OFF											
★ Reject US\$ 5		ON										
★ Accept US\$ 5		OFF										
★ Reject US\$ 10			ON									
★ Accept US\$ 10			OFF									
★ Reject US\$ 20				ON								
★ Accept US\$ 20				OFF								
★ Reject US\$ 50 & 100					ON							
★ Accept US\$ 50 & 100					OFF							
★ Reserved						ON						
★ Reserved						OFF						
<b>Pulse Mode</b>	<b>Other Mode</b>											
★ Harness Disable	BA stops working when fishing					ON						
★ Harness Enable	Normal					OFF						
★ Inhibit Active High							ON					
★ Inhibit Active Low							OFF					
★ 1 pulse / US\$ 1									OFF	OFF		
★ 2 pulse / US\$ 1									ON	OFF		
★ 4 pulse / US\$ 1									OFF	ON		
★ 20 pulse / US\$ 1									ON	ON		
★ Interface Timing Conversion	50ms LO / 50ms HI							OFF	OFF			
	60ms LO / 300ms HI							ON	OFF			
	30ms LO / 50ms HI							OFF	ON			
	150ms LO / 150ms HI							ON	ON			

★ Manufacture setting

◆ Note : (1) Reset the bill acceptor after setting the dip switch.

(2) SW7 and SW8 of the 8-switch DIP and the 4-switch DIP are for pulse protocol only.

## TAO-V-USD6(Pulse/MDB)

### Interface Settings: 2(Pulse)

INTERFACE	SW1	SW2	SW3	SW4
★ Credit-Pulse Normal HIGH	ON			
Credit-Pulse Normal LOW	OFF			
★ Pulse Mode		ON		
MDB Interface		OFF		
★ Reserved			ON	
			OFF	
				ON
				OFF

★ Manufacture setting

### Interface Settings: 2(MDB)

INTERFACE	SW1	SW2	SW3	SW4
★ Scaling Factor (SF) = 100 Decimal Point Position (DPP) = 2	ON			
Scaling Factor (SF) = 1 Decimal Point Position (DPP) = 0	OFF			
★ Pulse Mode		ON		
★ MDB Interface		OFF		
★ Reserved			ON	
			OFF	
				ON
				OFF

★ Manufacture setting

### Currency Assign Data

Interface Bill value	Pulse	MDB
BV1	US\$ 1	US\$ 1
BV2	US\$ 5	
BV3	US\$ 10	US\$ 5
BV4	US\$ 20	US\$ 10
BV5	US\$ 50	US\$ 20
BV6	US\$ 100	US\$ 50
BV7		US\$ 100