

## TAO-V-USD6

### TAO-V Option Switch Settings: 1(Pulse/MDB)

Supported bill US\$ 1, 2, 5, 10, 20, 50 6bills.

TAO-V dip-switch settings and functions:

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW1	SW2	SW3	SW4	
★ Reject US\$ 1	ON												
★ Accept US\$ 1	OFF												
★ Reject US\$ 2		ON											
★ Accept US\$ 2		OFF											
★ Reject US\$ 5 & 10			ON										
★ Accept US\$ 5 & 10			OFF										
★ Reject US\$ 20				ON									
★ Accept US\$ 20				OFF									
★ Reject US\$ 50					ON								
★ Accept US\$ 50					OFF								
★ Reserved						ON							
★ Reserved						OFF							
<b>Pulse Mode</b>	<b>Other Mode</b>												
★ Harness Disable	BA stops working when fishing						ON						
★ Harness Enable	Normal						OFF						
★ Inhibit Active High							ON						
★ Inhibit Active Low							OFF						
★ 1 pulse / US\$ 1								OFF	OFF				
2 pulse / US\$ 1								ON	OFF				
4 pulse / US\$ 1								OFF	ON				
20 pulse / US\$ 1								ON	ON				
★ Interface Timing Conversion	50ms LO / 50ms HI								OFF	OFF			
	60ms LO / 300ms HI								ON	OFF			
	30ms LO / 50ms HI								OFF	ON			
	150ms LO / 150ms HI								ON	ON			

★ Manufacture setting

◆ Note : (1) Default setting.

(2) Use 2nd and 3rd dip of the internal dip-switch to change different interface protocol.

## Appendix

## TAO-V-USD6(Pulse/MDB)

### Interface Settings: 2(Pulse)

INTERFACE	SW1	SW2	SW3	SW4
★ Credit-Pulse Normal HIGH	ON			
Credit-Pulse Normal LOW	OFF			
★ Pulse Mode		ON		
MDB Interface		OFF		
★ Reserved			ON	
			OFF	
				ON
				OFF

★ Manufacture setting

### Interface Settings: 2(MDB)

INTERFACE	SW1	SW2	SW3	SW4
★ Scaling Factor (SF) = 100 Decimal Point Position (DPP) = 2	ON			
Scaling Factor (SF) = 1 Decimal Point Position (DPP) = 0	OFF			
★ Pulse Mode		ON		
MDB Interface		OFF		
★ Reserved			ON	
			OFF	
				ON
				OFF

★ Manufacture setting

### Currency Assign Data

Interface Bill value	Pulse	MDB
BV1	US\$ 1	US\$ 1
BV2	US\$ 2	US\$ 2
BV3	US\$ 5	US\$ 5
BV4	US\$ 10	US\$ 10
BV5	US\$ 20	US\$ 20
BV6	US\$ 50	US\$ 50