

A6E/V6E Series

Bill Acceptor

- Auto-calibrating.
- Four-way bill insertion.
- Numerous interfaces available.
- High acceptance rate up to 96%.
- Easy installation and maintenance.



ICT

A6E/V6E Series

Bill Acceptor

A6E/V6E Series is a bill acceptor which features not only high-security module with bill box but also outstanding recognition, acceptance rate up to 96% or even greater.

Specifications



Acceptance Rate

96% or greater



Acceptance Speed

Approx. 3 sec. to cashbox



Bill Insertion

Four-way



Interface

A6E: Standard Pulse, 5V Enable, ICT Protocol.
V6E: MDB



Bill Width Accepted

60~67 mm/ 2.36~2.63 inches



Power Source

A6E: 12V DC (11.4~12.6V DC)
117V AC (105.3~128.7V AC)
V6E: 24V/34V DC (20V~42.5V DC)



Capacity

Approx. 100 bills (40~ 140)
300 bills (200~ 300)
500 bills (300~ 500)
550 bills (440~ 640)
800 bills (750~ 850)
1000 bills (1000~1140)



Power Consumption

A6E: 12V DC	Standby : 0.3A, 4W
	Operation: 0.9 A, 11W
	Maximum: 2.6A, 32W
117V AC	Standby : 0.06A, 7W
	Operation: 0.112A, 14W
	Maximum: 0.4A, 47W
V6E: 24V/34V DC	Standby : 0.15A, 6W
	Operation: 0.4A, 14W
	Maximum: 1.35A, 46W



Dimension

100 bills:
(W)94 x (D)91 x (H)235.9 mm/
(W)3.70 x (D)3.58 x (H)9.28 inches

300 bills:
(W)94 x (D)115 x (H)235.9 mm/
(W)3.70 x (D)4.53 x (H)9.28 inches

500 bills:
(W)94 x (D)130 x (H)235.9 mm/
(W)3.70 x (D)5.12 x (H)9.28 inches

550 bills:
(W)94 x (D)153 x (H)235.9 mm/
(W)3.70 x (D)6.02 x (H)9.28 inches

800 bills:
(W)94 x (D)190 x (H)235.9 mm/
(W)3.70 x (D)7.48 x (H)9.28 inches

1000 bills:
(W)94 x (D)232 x (H)235.9 mm/
(W)3.70 x (D)9.13 x (H)9.28 inches



Weight

Approx. 2 kg/ 4.4 lbs



Environmental

Operating Temperature:
0°C/ 32°F ~ 55 °C/ 131°F
Storage Temperature:
-30°C /-22 °F~ 70 °C/ 158°F
Humidity: 30%~85% RH (No Condensation)



Recommended Applications

Indoor Vending, Gaming, Amusement

Specifications are subject to change without prior notice.



International Currency Technologies

No.28, Ln. 15, Sec. 6, Minquan E. Rd., Neihu Dist., Taipei City 114, Taiwan

Phone: +886-2-2793-1236

Fax: +886-2-2793-6125

Email: sales@ictgroup.com.tw (Product Information)

fae@ictgroup.com.tw (Technical Service)

Website: www.ictgroup.com.tw