

MTB

Multi-function ToolBox

- Firmware download, Coin Changer (Recycler) operational setting, IrDA download/ reading audit data, and sensor calibration.
- High convenience: storage several firmwares at one time.
- Built-in memory and Micro-SD Card slot for large data storage.
- Chargeable battery and power saving design.
- One multi-purpose cable for different ICT products.
- Large screen to show information.
- Friendly user interface.
- Easy to carry.



The logo for ICT, featuring the letters 'iCT' in a bold, blue, sans-serif font. The 'i' has a red dot above it. The logo is set against a dark blue background with a pattern of white circles and lines.

Multi-function ToolBox

MTB (Multi-function ToolBox) is a total solution for ICT product maintenance. The portable programmer-MTB, presents data in a large LCM makes product maintenance easily and fast. MTB is high convenience that could storage several firmwares at the same time. Powerful multi functions include programmer, changer operation, IrDA download / reading audit data and sensor calibration. All-in-one design meets all requirements form market.

Specifications



Download Programmer

Bill Acceptor:

A / V Series, BR2300, BS7, E77, Envy Series, K77, L Series, LV77 Series, LX7, NK Series, NBA, NE77, P Series, PA7, PL77, S Series, S7ER, S7A2, TAO Light, TAO-AV, V7E, V77E, V7P, XBA, X7P.

Coin Changer:
CC6100

CA:
UCA, SCA.

Others:
CVD, CSD, GP58 CR/CA, Mini hopper.



Power/Battery Information

Power supply from the embedded rechargeable Li-ion battery.

Power saving design for extended battery sustainability.

Battery charging through PC(USB port) or external adapter(DC 5V, 500mA or above)

Capacity: 2100 mAh

Continue working time: up to 6 hrs

Charging time: 4hrs (Capacity 0%~100%)



Memory Device

Built-in memory (4M Byte)

Micro-SD Card slot for large data storage.
(Up to 32 GB)



Power Consumption

Standby: 3.7V, 350mA, 1.30W

Operation: 3.7V, 370mA, 1.40W

Maximum: 3.7V, 2A, 7.40W



Dimension

(L×W×T) 170×100.4×33 mm/

(L×W×T) .69×3.95×1.29 inch



Weight

Approx. 288.5g / 0.637 lbs



Environmental

Operating Temperature: -5°C~50°

Storage Temperature: -20°C~70°C

Operating Humidity: 85%RH(no condensation)

Battery in charge Temperature: 0°C~45°C



Recommended Applications

Portable device



Specifications are subject to change without prior notice.



International Currency Technologies

No.28, Ln. 15, Sec. 6, Minquan E. Rd., Neihu Dist., Taipei City 114, Taiwan

Phone: +886-2-2793-1236

Fax: +886-2-2793-6125

Email: sales@ictgroup.com.tw (Product Information)

fae@ictgroup.com.tw (Technical Service)

Website: www.ictgroup.com.tw